

SMART GRID COMMUNICATION SYSTEM USING LORA AND MQTT PROTOCOLS

Jayabharathi S, Niranjana V, Rupasree P, IV-EEE Students,
Mr.R.Manikandan,M.E.,(Ph.D).,AP/Department of EEE
Vivekanandha College of Engineering for Women (Autonomous),Tiruchengode
niranjanaaveerasamy30@gmail.com

Abstract:

This paper presents a Smart Grid Communication System using LoRa and MQTT protocols to achieve reliable, low- power, and long-range data transmission for modern power networks. The proposed system enables real-time monitoring and control of smart grid components through an IoT-based communication framework. LoRa technology is utilized to provide energy-efficient wireless communication between field devices and gateways over long distances. The MQTT protocol ensures lightweight, fast, and secure data exchange between gateways and cloud servers. The system supports bidirectional communication, allowing remote monitoring, control, and automation of grid operations. Key grid parameters such as voltage, current, power consumption, and device status are continuously collected and transmitted. A cloud-based platform is integrated for data storage, visualization, and performance analysis. The design improves scalability while reducing communication cost and infrastructure complexity. Performance evaluation demonstrates enhanced reliability, low latency, and reduced power consumption compared to conventional methods. The proposed approach offers a practical and scalable solution for intelligent monitoring and automation in smart grid environments.

Keywords: Smart Grid, LoRa, MQTT Protocol, Internet of Things (IoT), Wireless Communication, Energy Monitoring, Bidirectional Communication, Cloud Computing, Smart Metering, Power System Automation.

1.INTRODUCTION

The modern electrical power system is undergoing a major transformation toward smart grid technology to improve efficiency, reliability, and sustainability. Unlike conventional grids, smart grids integrate advanced communication, control, and monitoring technologies to enable real-time interaction between power generation, distribution, and consumers. This evolution is driven by the increasing penetration of renewable energy sources, distributed generation systems, and intelligent electronic devices. As a result, a robust and efficient communication infrastructure has become a fundamental requirement for the successful operation of smart grids.

One of the major challenges in smart grid implementation is establishing a communication system that is reliable, energy-efficient, cost-effective, and capable of covering large geographical areas. Traditional communication technologies such as GSM, Wi-Fi, and ZigBee often face limitations including high power consumption, limited range, network congestion, and infrastructure complexity. These limitations make them less suitable for remote monitoring and control of distributed grid assets such as smart meters, transformers, and renewable energy systems located in rural or wide- area environments.

To address these challenges, Low Power Wide Area Network (LPWAN) technologies, particularly LoRa (Long Range communication),

have emerged as a promising solution. LoRa offers long- distance communication with very low power consumption, making it ideal for battery-powered grid sensors and monitoring devices. However, long-range communication alone is not sufficient; efficient data transfer to cloud platforms and control centers is equally important. This is where the MQTT (Message Queuing Telemetry Transport) protocol plays a crucial role. MQTT is a lightweight, publish–subscribe messaging protocol designed for IoT applications, ensuring fast, reliable, and low-bandwidth data exchange.

In this context, this paper proposes a Smart Grid Communication System that integrates LoRa and MQTT protocols to provide a scalable and intelligent communication framework. The system enables real-time monitoring, remote control, and automation of grid operations through cloud-based platforms. By combining long-range wireless communication with efficient IoT messaging, the proposed approach enhances system reliability, reduces operational costs, and supports the development of future intelligent energy networks.

2. LITERATURE REVIEW

Communication technology plays a crucial role in the development of smart grid systems, and numerous studies have explored different approaches to achieve reliable data transmission. Early smart grid communication systems primarily relied on technologies such as Power Line Communication (PLC), GSM, ZigBee, and Wi-Fi. PLC utilizes existing power lines for data transmission but suffers from noise interference and limited bandwidth. GSM-based systems offer wide coverage but involve higher operational costs and latency issues. ZigBee and Wi-Fi are suitable for short-range communication; however, they face limitations in terms of range, power consumption, and scalability when deployed in

large-area smart grid environments.

With the advancement of Internet of Things (IoT) technologies, researchers have shifted focus toward Low Power Wide Area Network (LPWAN) solutions. Among these, LoRa has gained significant attention due to its long communication range, low energy consumption, and ability to support a large number of devices. Several works have demonstrated the effectiveness of LoRa in smart metering, environmental monitoring, and remote energy management systems. Studies report that LoRa can achieve communication over several kilometers while maintaining minimal power usage, making it ideal for distributed grid monitoring in rural and semi-urban regions.

Parallel to the development of LPWAN technologies, lightweight messaging protocols have been explored for cloud- based smart grid applications. MQTT has emerged as one of the most preferred protocols due to its publish–subscribe architecture, low bandwidth requirement, and reliable message delivery.

Research indicates that MQTT significantly reduces communication overhead compared to HTTP-based systems and ensures efficient real-time data transfer in IoT networks. It has been successfully applied in industrial automation, home energy management, and remote sensing applications.

Although individual use of LoRa and MQTT has been widely studied, the integration of both technologies for a unified smart grid communication framework is still evolving.

Existing systems often lack a comprehensive approach that combines long-range field communication with efficient cloud data handling. Therefore, this work focuses on integrating LoRa for device-to-gateway communication and MQTT

for gateway-to-cloud data transmission, aiming to provide a scalable, low-cost, and energy-efficient communication solution tailored for modern smart grid applications.

3.METHODOLOGY

Sensors installed at different grid nodes continuously measure electrical parameters such as voltage, current, power, and energy consumption.

The collected analog signals are converted into digital values and sent to a microcontroller, which processes, filters, and formats the data for transmission.

A LoRa transmitter module then sends this information wirelessly over long distances to a central LoRa gateway with minimal power usage.

The gateway acts as a bridge, forwarding the received data to an MQTT broker through the internet for cloud communication. The cloud server stores the data in databases and displays it on a real-time dashboard for monitoring and analysis.

When control actions are required, commands from the cloud are sent back through the MQTT broker to the gateway, which relays them via LoRa to the respective field devices for proper grid operation and automation.

4.EXISTING SYSTEM

Traditional smart grid communication systems mainly rely on technologies such as GSM, Wi-Fi, ZigBee, and Power Line Communication (PLC) for data transmission between grid components and control centers. While these methods enable basic monitoring and control, they suffer from several limitations including high power consumption, limited

communication range, network congestion, and increased infrastructure cost. Short-range technologies like ZigBee and Wi-Fi are not suitable for wide-area grid coverage, especially in rural and remote locations. GSM-based systems introduce

latency and recurring operational expenses, while PLC is affected by electrical noise and signal attenuation over long distances. These challenges reduce communication reliability and scalability, making conventional systems less efficient for modern smart grid applications that require real-time, long-distance, and low-power communication.

5.PROPOSED SYSTEM

The proposed system introduces a Smart Grid Communication framework that integrates LoRa and MQTT protocols to achieve reliable, long-range, and energy-efficient data transmission.

Field sensors installed at various grid nodes measure electrical parameters such as voltage, current, and power consumption, which are processed by a microcontroller.

The data is transmitted wirelessly over long distances using LoRa technology to a central gateway.

The gateway then forwards the information to a cloud server through the MQTT protocol, enabling lightweight, secure, and real-time communication. A cloud-based dashboard is used for monitoring, analysis, and data storage.

The system also supports bidirectional communication, allowing control commands from the cloud to be sent back to field devices for automation and grid management.

This approach improves scalability, reduces operational cost, and ensures reliable

communication for modern smart grid environments.

6. BLOCK DIAGRAM




FIG-1

7. SYSTEM DESIGN

A smart grid communication system using LoRa and MQTT protocols is designed to enable reliable and long-range data communication between smart meters and the utility control center. Smart meters and grid sensors collect real-time data such as voltage, current, power consumption, and fault status. These devices are connected to LoRa nodes, which transmit the collected data wirelessly over long distances with low power consumption. Multiple LoRa nodes communicate with a LoRa gateway, which acts as a bridge between field devices and the central network, making the system suitable for wide-area and remote grid monitoring.

The LoRa gateway forwards the received data

to a cloud or server platform using the MQTT protocol, which follows a lightweight publish-subscribe model. In this design, smart grid data is published to

specific MQTT topics, and the utility control center subscribes to these topics to receive real-time updates. manages message delivery efficiently, ensuring low latency and reliable communication.

This system design supports scalable monitoring, efficient energy management, and quick fault detection while maintaining low operational cost and power usage.

8. PROTOTYPE



9. LORA TECHNOLOGY

The smart grid communication system using LoRa technology and MQTT protocols is designed to monitor and manage electrical grid parameters efficiently over long distances. In this model, smart meters and grid sensors are installed at consumer and distribution points to measure parameters such as energy consumption, voltage, current, and power quality. These sensors are connected to LoRa-based end nodes, which transmit the collected data wirelessly using LoRa modulation. Due to its long-range and

low-power characteristics, LoRa technology enables reliable communication even in remote and wide-area grid environments.

The transmitted data from LoRa end nodes is received by a LoRa gateway, which aggregates data from multiple nodes and forwards it to a central server or cloud platform. The gateway uses the MQTT protocol to publish the received data to an MQTT broker, where the utility control center subscribes to relevant topics for real-time monitoring and analysis. This model ensures scalable, secure, and low-latency communication, supporting efficient energy management, fault detection, and improved decision-making in smart grid operations.

10. RESULT

The implementation of LoRa technology in the smart grid communication system demonstrates reliable long-range and low-power data transmission between smart meters and the control center. Experimental results show that grid parameters such as voltage, current, and energy consumption are successfully transmitted over long distances with minimal packet loss. The system operates efficiently even in remote and low-infrastructure areas, proving the suitability of LoRa for wide-area smart grid monitoring while maintaining low power consumption at sensor nodes.

The integration of the MQTT protocol further improves system performance by enabling fast and lightweight data exchange between the LoRa gateway and the cloud server. Results indicate reduced communication latency, efficient message delivery, and better scalability as the number of smart meters increases. Real-

time monitoring and data visualization at the utility side allow quick fault detection and improved energy management. Overall, the results confirm that combining LoRa technology with

MQTT provides a cost-effective, scalable, and reliable communication solution for smart grid applications.

11. CONCLUSION

The smart grid communication system using LoRa and MQTT protocols provides an efficient and reliable solution for long-range data communication in modern power distribution networks. By utilizing LoRa technology, the system achieves low-power and wide-area connectivity between smart meters and grid sensors, making it suitable for remote and large-scale deployments. This approach enables continuous monitoring of energy consumption and grid parameters, improving the overall visibility and control of the electrical grid.

The use of the MQTT protocol enhances data transmission by offering a lightweight and scalable communication model between the gateway and the control center. It ensures timely delivery of data with minimal latency and supports the integration of cloud-based monitoring and analytics. Overall, the proposed system improves energy management, fault detection, and operational efficiency, demonstrating that the combination of LoRa and MQTT is a cost-effective and scalable solution for smart grid communication systems..

12. FUTURE SCOPE

The future scope of the smart grid communication system using LoRa and MQTT protocols includes large-scale deployment across urban and rural power distribution networks. By integrating advanced sensors and smart meters, the system can support real-time monitoring of renewable energy sources such as solar and wind power. Enhanced data analytics and cloud-based platforms can further improve load forecasting, energy optimization, and predictive maintenance, leading to more reliable and efficient grid operations.

In the future, the system can be expanded by incorporating artificial intelligence and machine learning techniques for automated fault detection and decision-making. Improved security mechanisms such as encryption and authentication can be implemented to ensure secure data transmission. Additionally, integration with mobile applications and smart home systems will allow consumers to monitor and manage their energy usage more effectively, making the smart grid more intelligent, secure, and user-friendly.

13. REFERENCES

- [1] IoT Based Smart Energy Meter”, Birendrakumar Sahani, Tejashree Ravi, Akibjaved Tamboli, (2017), International Research Journal of Engineering and Technology (IRJET), Volume: 04, Issue: 04.
- [2] “Smart Energy Metering and Power Theft Control using Arduino & GSM”, Visalatchi S, Kamal Sandeep K, (April 2017), Institute of Electrical and Electronics Engineers (IEEE).
- [3] “Smart Energy Meter”, Brinda.S, Vishal Kumar Sah, Jaladi Harish, (2018), International Journal of Engineering Science and Computing (IJESC)Volume 8, Issue 3.
- [4] “IOT Based Smart Energy Meter for Efficient Energy Utilization in Smart Grid”, Bibek Kanti Barman, Shiv Nath Yadav, Shivam Kumar, (2018), Institute of Electrical and Electronics Engineers (IEEE).
- [5] IoT Based Smart Energy Meter”, Birendrakumar Sahani, Tejashree Ravi, Akibjaved Tamboli, (2017), International Research Journal of Engineering and Technology (IRJET), Volume: 04, Issue: 04.
- [6] “Smart Energy Metering and Power Theft Control using Arduino & GSM”, Visalatchi S, Kamal Sandeep K, (April 2017), Institute of Electrical and Electronics Engineers (IEEE).
- [7] “Smart Energy Meter”, Brinda.S, Vishal Kumar Sah, Jaladi Harish, (2018), International Journal of Engineering Science and Computing

(IJESC)Volume 8, Issue 3.

- [8] “IOT Based Smart Energy Meter for Efficient Energy Utilization in Smart Grid”, Bibek Kanti Barman, Shiv Nath Yadav, Shivam Kumar, (2018), Institute of Electrical and Electronics Engineers (IEEE).